

**ANTI STAIN AQUA 5200**
primer

PAINT TYPE	Water-borne primer for wooden surfaces, based on acrylic.
USAGE	Wooden window frames and external doors. Before using the product, the manufacturer should be contacted to check the suitability of the product for the object in question.
PROPERTIES	ANTI STAIN AQUA 5200 provides good adhesion and it dries quickly. It will slow down the yellowing of knots. ANTI STAIN AQUA 5200-00 is applied by spray. ANTI STAIN AQUA 5200-01 is applied by flow-coat.

TECHNICAL DATA

Solids	35 ±2% by volume
Total mass of solids	abt. 580 g/l
Volatile organic compound (VOC)	abt. 50 g/l
Drying time, +23°C, relative humidity 50% (glass plate 120 µm)	
- dust free	after 20 min
- touch dry	after 2 h
	The drying times given are indicative because the product is intended for use on wooden substrates.
- fit for sanding on wood	after 4 h
Thinner, clean up	Water
Colours	White

PTO

DIRECTION FOR USE**Surface preparation**

The surface must be clean and dry.
The moisture content of the wood is to be below 20%.
It is recommended that the wood is treated with an efficient wood preservative that protects it against rot, blue stain fungi and mildew.

Application conditions

The temperature of the air, the surface and the paint shall be above +15°C and the relative humidity of the air below 80% during the time of application and drying.

The best result is achieved when the temperature of the air is +23 - +38°C, the relative humidity of the air 50 - 70% and the ventilation is good.

Application

Before use stir the paint thoroughly.

Apply ANTI STAIN AQUA 5200-00 with a spray.

ANTI STAIN AQUA 5200-01 is applied by flow-coat.

The recommended wet film thickness is 100 - 150 µm.

STORAGE

Must not freeze. The best storage temperature is between +10 - +25°C.

The information of this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.
